NSN 4820-01-124-8238

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-124-8238

Poppet						
Valve Discharge Flow Rate:						
13500.0 pounds per hour						
Bolt Hole Quantity:						
8 all ends						
Maximum Operating Temp:						
425.0 degrees fahrenheit single response						
Valve Operation Method:						
Automatic						
Flange Shape:						
Round with holes all ends						
Connection Type:						
Flange all ends						
Valve Size:						
3.500 inches						
Maximum Operating Pressure:						
50.0 pounds per square inch single response						
Opening Pressure Setting:						
30.0 pounds per square inch						
Outside Diameter:						
7.187 inches all ends						
Thickness:						
0.562 inches all ends						
First Connection Face To Centerline Distance:						
7.187 inches						
Bolt Hole Diameter:						
0.562 inches all ends						
Second Connection Face To Centerline Distance:						
7.187 inches						
Bolt Circle Diameter:						
6.062 inches all ends						
Flange Face Design:						
Plain all ends						
Material:						
Stainless steel stem						
Media For Which Designed:						
Water-oil-gas single response						
Style Designator:						
Err-090						
Shelf Life:						
N/a						

NSN 4820-01-124-8238

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A046b0