# NSN 4820-01-124-8238

Safety Relief Valve - Page 1 of 2





## Flow Control Device:

Poppet

Valve Discharge Flow Rate:

13500.0 pounds per hour

# **Bolt Hole Quantity:**

8 all ends

## Maximum Operating Temp:

425.0 degrees fahrenheit single response

### Valve Operation Method:

Automatic

Flange Shape:

Round with holes all ends

#### **Connection Type:**

Flange all ends

Valve Size:

3.500 inches

### Maximum Operating Pressure:

50.0 pounds per square inch single response

### **Opening Pressure Setting:**

30.0 pounds per square inch

## **Outside Diameter:**

7.187 inches all ends

#### Thickness:

0.562 inches all ends

## First Connection Face To Centerline Distance:

7.187 inches

## **Bolt Hole Diameter:**

0.562 inches all ends

### Second Connection Face To Centerline Distance:

7.187 inches

#### **Bolt Circle Diameter:**

6.062 inches all ends

### Flange Face Design:

Plain all ends

### Material:

Stainless steel stem

### Media For Which Designed:

Water-oil-gas single response

## Style Designator:

Err-090

## Shelf Life:

N/a

# NSN 4820-01-124-8238

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

