## NSN 4820-01-125-5454

Safety Relief Valve - Page 1 of 2

Thread Class: 3a all ends



View Online at https://aerobasegroup.com/nsn/4820-01-125-5454

Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Minimum Operating Temp:
-65.0 degrees fahrenheit
Connection Style:
G46a plain (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube all ends
Maximum Operating Pressure:
Maximum Operating Pressure: 200.0 pounds per square inch single response
200.0 pounds per square inch single response
200.0 pounds per square inch single response  Thread Size:
200.0 pounds per square inch single response  Thread Size:  0.438 inches all ends
200.0 pounds per square inch single response  Thread Size:  0.438 inches all ends  Opening Pressure Setting:
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch  Material:
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch  Material:  Steel comp 303 seat
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch  Material:  Steel comp 303 seat  Media For Which Designed:
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch  Material: Steel comp 303 seat  Media For Which Designed: Oxygen, gaseous 3rd response
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch  Material: Steel comp 303 seat  Media For Which Designed: Oxygen, gaseous 3rd response  Style Designator:
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch  Material: Steel comp 303 seat  Media For Which Designed: Oxygen, gaseous 3rd response  Style Designator:  Err-090
200.0 pounds per square inch single response  Thread Size: 0.438 inches all ends  Opening Pressure Setting: 16.0 pounds per square inch  Material: Steel comp 303 seat  Media For Which Designed: Oxygen, gaseous 3rd response  Style Designator: Err-090  Thread Series Designator:
Thread Size: 0.438 inches all ends Opening Pressure Setting: 16.0 pounds per square inch Material: Steel comp 303 seat Media For Which Designed: Oxygen, gaseous 3rd response Style Designator: Err-090 Thread Series Designator: Unjf all ends
Thread Size: 0.438 inches all ends Opening Pressure Setting: 16.0 pounds per square inch Material: Steel comp 303 seat Media For Which Designed: Oxygen, gaseous 3rd response Style Designator: Err-090 Thread Series Designator: Unjf all ends Furnished Items And Quantity:
200.0 pounds per square inch single response Thread Size: 0.438 inches all ends Opening Pressure Setting: 16.0 pounds per square inch Material: Steel comp 303 seat Media For Which Designed: Oxygen, gaseous 3rd response Style Designator: Err-090 Thread Series Designator: Unjf all ends Furnished Items And Quantity: 1 deflector cap
Thread Size: 0.438 inches all ends Opening Pressure Setting: 16.0 pounds per square inch Material: Steel comp 303 seat Media For Which Designed: Oxygen, gaseous 3rd response Style Designator: Err-090 Thread Series Designator: Unjf all ends Furnished Items And Quantity: 1 deflector cap Shelf Life:

## NSN 4820-01-125-5454

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0