NSN 4820-01-126-9701

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-126-9701 Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method: Bolted Maximum Operating Temp:** 150.0 degrees fahrenheit single response **End Application:** Los angeles class ss (688) **Valve Operation Method:** Automatic Flange Shape: Round all ends **Connection Type:** Flange all ends Valve Size: 2.500 inches **Adjustable Pressure Range:** +30.0/+34.0 pounds per square inch **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Outside Diameter:** 6.125 inches all ends Thickness: 0.500 inches all ends **First Connection Face To Centerline Distance:** 5.500 inches **Second Connection Face To Centerline Distance:** 5.500 inches Flange Face Design: Plain all ends Material: Nickel alloy flow control device **Material Specification:** Qq-c-390, alloy d4/d/ federal specification single material response body Media For Which Designed: Water, fresh single response **Style Designator:** Err-090

Shelf Life:

N/a

NSN 4820-01-126-9701

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0