# NSN 4820-01-127-3845

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-127-3845



# Flow Control Device: Disk

Bonnet Type:

Inside spring

### **Bonnet Attachment Method:**

Bolted

#### **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

150.0 degrees fahrenheit single response

#### **End Application:**

Los angeles class ss (688)

#### Valve Operation Method:

Automatic

### Flange Shape:

Round all ends

#### **Connection Type:**

Flange all ends

#### Valve Size:

3.000 inches

# Adjustable Pressure Range:

+136.0/+155.0 pounds per square inch

# Maximum Operating Pressure:

250.0 pounds per square inch single response

#### **Outside Diameter:**

6.250 inches all ends

#### Thickness:

0.938 inches all ends

# First Connection Face To Centerline Distance:

6.000 inches

# Second Connection Face To Centerline Distance:

6.000 inches

#### Flange Face Design:

Plain all ends

#### Material:

Nickel alloy flow control device

# Material Specification:

Qq-c-390, alloy d4/d/ federal specification single material response body

# Media For Which Designed:

Liquid, ingested single response

#### Style Designator:

Err-090

# NSN 4820-01-127-3845

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

