NSN 4820-01-127-3845

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-127-3845

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Los angeles class ss (688)
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
3.000 inches
Adjustable Pressure Range:
+136.0/+155.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
6.250 inches all ends
Thickness:
0.938 inches all ends
First Connection Face To Centerline Distance:
6.000 inches
Second Connection Face To Centerline Distance:
6.000 inches
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Material Specification:
Qq-c-390, alloy d4/d/ federal specification single material response body
Media For Which Designed:
Liquid, ingested single response
Style Designator:
Err-090

NSN 4820-01-127-3845

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0