NSN 4820-01-127-3846

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-127-3846

Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
End Application:
Los angeles class ss (688)
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+2.0/+13.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
5.000 inches all ends
Thickness:
0.690 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Second Connection Face To Centerline Distance:
4.750 inches
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
2.875 inches all ends
Material:
Steel seat
Material Specification:
Astm a276 type 303 assn standard single material response stem
Style Designator:
Err-090
Shelf Life:
N/a

NSN 4820-01-127-3846

Safety Relief Valve - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A046b0