NSN 4820-01-127-5114

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-127-5114

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+25.0/+29.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.440 inches all ends
First Connection Face To Centerline Distance:
3.250 inches
Bolt Hole Diameter:
0.620 inches all ends
Second Connection Face To Centerline Distance:
3.250 inches
Bolt Circle Diameter:
2.380 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends

NSN 4820-01-127-5114

Safety Relief Valve - Page 2 of 2



Raised Face Diameter:
1.190 inches all ends
Material:
Steel comp 303 stem
Material Specification:
Qq-n-281 federal specification single material response seat
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A046b0