NSN 4820-01-127-6671

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-127-6671

| Thread Class: |
|---|
| 3b 2nd end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Integral |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 450.0 degrees fahrenheit single response |
| Connection Style: |
| G4 gasket sea (boss) 2nd end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal boss 2nd end |
| Maximum Operating Pressure: |
| 2500.0 pounds per square inch single response |
| Thread Size: |
| 0.562 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Opening Pressure Setting: |
| 200.0 pounds per square inch |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Aisi 303 assn standard single material response |
| Media For Which Designed: |
| Gas, inert single response |
| Style Designator: |
| Err-090 |
| Thread Series Designator: |
| Unjf 2nd end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 4820-01-127-6671

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0