## NSN 4820-01-127-8627



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-01-127-8627 **Thread Direction:** Right-hand 2nd end Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Valve Discharge Flow Rate:** 20.0 gallons per minute Renewable Seat Ring Type: Retaining screw **Maximum Operating Temp:** 300.0 degrees fahrenheit single response **End Application:** Condensate tank waste heat recycling system p/n vp-cru-215-hp onboard 270 ft wmec class coast guard vessels **Connection Style:** Plain, optional en (pipe) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 2nd end **Maximum Operating Pressure:** 900.0 pounds per square inch single response **Thread Size:** 1.000 inches 2nd end **Opening Pressure Setting:** 35.0 pounds per square inch Material: Copper alloy body

Media For Which Designed:

Water-oil-gas single response

**Style Designator:** 

Angle

**Thread Series Designator:** 

Npt 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 4820-01-127-8627

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0