## NSN 4820-01-129-4544

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-129-4544

Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Los angeles class ss (688)
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+35.0/+44.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.500 inches 1st end
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.250 inches
Second Connection Face To Centerline Distance:
3.250 inches
Flange Face Design:
Raised straight 1st end
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.375 inches all ends
Material:
Steel flow control device
Material Specification:
Astm a216, grade wcb assn standard single material response body

## NSN 4820-01-129-4544

Safety Relief Valve - Page 2 of 2



Media For Which Designe	Which Designe	ed
-------------------------	---------------	----

Liquid, ingested single response

Style Designator:

Err-090

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A046b0