NSN 4820-01-129-5561

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Disk Loading Method:

Stem

Bolted

Bonnet Type: Inside spring



View Online at https://aerobasegroup.com/nsn/4820-01-129-5561

Spring
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
2.500 inches
Adjustable Pressure Range:
+56.0/+65.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thickness:
0.500 inches all ends
First Connection Face To Centerline Distance:
5.500 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
5.500 inches
Bolt Circle Diameter:
5.000 inches all ends
Flange Face Design:
Recessed straight 2nd end
Recess Diameter:
2.710 inches 2nd end
Material:
Nickel alloy stem
Media For Which Designed:
Oil 1st response

NSN 4820-01-129-5561

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0