NSN 4820-01-129-7664

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-129-7664

| Pipe Size Accommodated: |
|--|
| 2.000 inches all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Bolted |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 165.0 degrees fahrenheit single response |
| End Application: |
| Los angeles class ss (688) |
| Connection Style: |
| Streamlined with one brazing ring err-100 |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Unthreaded internal pipe all ends |
| Adjustable Pressure Range: |
| +351.0/+400.0 pounds per square inch |
| Maximum Operating Pressure: |
| 500.0 pounds per square inch single response |
| Material: |
| Steel comp 316 stem |
| Material Specification: |
| Qq-n-281 federal specification single material response stem |
| Media For Which Designed: |
| Gas, inert single response |
| Style Designator: |
| Err-090 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |