NSN 4820-01-130-2157

Safety Relief Valve - Page 1 of 2



calcity Honor valve in age in or a	
View Online at https://aerobasegroup.com/nsn/4820-01-130-2157	
Flow Control Device:	
Disk	
Bonnet Type:	
Inside spring	
Bonnet Attachment Method:	
Bolted	
Bolt Hole Quantity:	
8 all ends	
Maximum Operating Temp:	
425.0 degrees fahrenheit single response	
Valve Operation Method:	
Automatic	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
3.000 inches	
Adjustable Pressure Range:	
+5.0/+150.0 pounds per square inch	
Maximum Operating Pressure:	
150.0 pounds per square inch single response	
Outside Diameter:	
6.625 inches all ends	
Thickness:	
1.000 inches 1st end	
First Connection Face To Centerline Distance:	
6.000 inches	
Bolt Hole Diameter:	
0.562 inches all ends	
Second Connection Face To Centerline Distance:	
5.500 inches	
Bolt Circle Diameter:	
5.500 inches all ends	
Flange Face Design:	

Recessed straight 1st end

Recess Diameter:

3.000 inches 1st end

Material:

Steel comp 316 stem

Media For Which Designed:

Water-oil-gas 2nd response

NSN 4820-01-130-2157

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0