NSN 4820-01-130-3600

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-130-3600

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
425.0 degrees fahrenheit single response
End Application:
Combat system support equipment
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+20.0/+24.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
5.062 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Second Connection Face To Centerline Distance:
4.750 inches
Flange Face Design:
Plain all ends
Material:
Steel comp 316 stem
Material Specification:
Qq-c-390, alloy d4/d/ federal specification single material response seat
Media For Which Designed:
Air 1st response
Style Designator:
Err-090

NSN 4820-01-130-3600

Safety Relief Valve - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0