NSN 4820-01-130-4323

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-130-4323

Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+751.0/+1100.0 pounds per square inch
Maximum Operating Pressure:
700.0 pounds per square inch single response
Outside Diameter:
3.812 inches all ends
Thickness:
0.688 inches all ends
First Connection Face To Centerline Distance:
3.000 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.000 inches
Bolt Circle Diameter:
2.688 inches all ends
Flange Face Design:
Plain all ends
Material:
Steel comp 316 stem
Material Specification:
Qq-c-390, alloy d4/d/ federal specification single material response body
Media For Which Designed:
Water, fresh single response

NSN 4820-01-130-4323

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0