NSN 4820-01-130-5373

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-130-5373	
Flow Control Device:	
Disk	
Bonnet Type:	
Outside screw-yoke	
Bonnet Attachment Method:	
Bolted	
Bolt Hole Quantity:	
4 all ends	
Maximum Operating Temp:	
775.0 degrees fahrenheit single response	
Valve Operation Method:	
Manual	
Flange Shape:	
Round with holes all ends	
Connection Type:	
Flange all ends	
Valve Size:	
1.250 inches	
Maximum Operating Pressure:	
1500.0 pounds per square inch single response	
Outside Diameter:	
6.250 inches all ends	
Face To Face Distance:	
11.000 inches	
Thickness:	
1.125 inches all ends	
Bolt Hole Diameter:	
1.000 inches all ends	
Bolt Circle Diameter:	
4.375 inches all ends	
Flange Face Design:	
Raised straight all ends	
Raised Face Height:	
0.250 inches all ends	

_ . ._ _ . .

Raised Face Diameter:

2.500 inches all ends

Special Features:

Stop valve type; centerless ground and hardened stems

Material:

Stainless steel flow control device

Material Specification:

Astm a105, grade 2 assn standard single material response body

NSN 4820-01-130-5373

Globe Valve - Page 2 of 2



Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Furnished Items And Quantity:
1 handwheel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0