NSN 4820-01-130-5381

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-130-5381

Pipe Size Accommodated:
0.250 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
30.0 gallons per minute
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Bonnet packing
Adjustable Pressure Range:
+401.0/+500.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Material:
Rubber packing
Material Specification:
Qq-n-281 federal specification single material response stem
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Furnished Items And Quantity:
2 tailpiece and 2 nut
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 4820-01-130-5381

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-p-5516 spec.