

View Online at <https://aerobasegroup.com/nsn/4820-01-130-6611>

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Bolted

**Disk Loading Method:**

Spring

**Bolt Hole Quantity:**

4 all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

Los angeles class ss (688) ; whidbey island class lsd

**Valve Operation Method:**

Automatic

**Flange Shape:**

Round all ends

**Connection Type:**

Flange all ends

**Valve Size:**

2.500 inches

**Adjustable Pressure Range:**

+45.0/+55.0 pounds per square inch

**Maximum Operating Pressure:**

150.0 pounds per square inch single response

**Criticality Code Justification:**

Feat

**Outside Diameter:**

7.000 inches all ends

**Thickness:**

0.875 inches all ends

**First Connection Face To Centerline Distance:**

5.500 inches

**Bolt Hole Diameter:**

0.750 inches all ends

**Second Connection Face To Centerline Distance:**

5.500 inches

**Bolt Circle Diameter:**

5.500 inches all ends

**Flange Face Design:**

Raised straight all ends

**Raised Face Height:**

0.062 inches all ends

**Raised Face Diameter:**

4.125 inches all ends

**Special Features:**

Weapon system essential

**Material:**

Steel

**Style Designator:**

Err-090

**Furnished Items And Quantity:**

1 lever

**Specification Data:**

81349-mil-v-24332 government specification

**Specification Or Standard:**

A grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-v-24332 spec.