## NSN 4820-01-130-6612

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-130-6612 **Thread Class:** 2a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring **Maximum Operating Temp:** 425.0 degrees fahrenheit single response **Connection Style:** G50 external seat for gasket seal (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external boss all ends Thready Qty Per Inch (tpi): 12 all ends **Adjustable Pressure Range:** +45.0/+55.0 pounds per square inch **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 1.187 inches all ends **Special Features:** Top guided Material: Rubber butadiene-acrylonitrile class nbr seat **Material Specification:** Qq-n-281 federal specification single material response flow control device Media For Which Designed: Air 1st response **Style Designator:** Err-090

**Thread Series Designator:** 

Un all ends

**Furnished Items And Quantity:** 

2 nut and 2 tailpiece

## NSN 4820-01-130-6612

Safety Relief Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0