## NSN 4820-01-130-6613

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-130-6613

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Streamlined with one brazing ring err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe 2nd end
Thready Qty Per Inch (tpi):
16 1st end
Adjustable Pressure Range:
+351.0/+400.0 pounds per square inch
<b>Maximum Operating Pressure:</b>
1500.0 pounds per square inch single response
Thread Size:
0.312 inches 1st end
Material:
Nickel alloy flow control device
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Thread Series Designator:
Uns 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-130-6613

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0