NSN 4820-01-130-8753

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-130-8753

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
10.0 gallons per minute
Bolt Hole Quantity:
3 all ends
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Pressure tight outlet side
Valve Size:
0.500 inches
Adjustable Pressure Range:
+30.0/+34.0 pounds per square inch
Outside Diameter:
3.550 inches all ends
Thickness:
0.408 inches all ends
First Connection Face To Centerline Distance:
3.500 inches
Bolt Hole Diameter:
0.568 inches all ends
Second Connection Face To Centerline Distance:
3.500 inches
Bolt Circle Diameter:
2.418 inches all ends
Flange Face Design:
Plain all ends
Material:
Stainless steel seat

NSN 4820-01-130-8753

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0