NSN 4820-01-131-0229

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-131-0229

Exposed spring Bonnet Attachment Method: Bolted
Bolted
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Nimitzlass cvn
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+15.0/+19.0 pounds per square inch
Maximum Operating Pressure:
275.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.376 inches all ends
First Connection Face To Centerline Distance:
3.250 inches
Second Connection Face To Centerline Distance:
3.250 inches
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.375 inches all ends
Material:
Steel comp 304 stem
Steel comp 304 stem Material Specification:
·
Material Specification:

NSN 4820-01-131-0229

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Shelf Life:

N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0