NSN 4820-01-131-0230

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-131-0230

Pipe Size Accommodated:				
0.500 inches all ends				
Flow Control Device:				
Disk				
Bonnet Type:				
Inside spring				
Bonnet Attachment Method:				
Bolted				
Disk Loading Method:				
Spring				
Maximum Operating Temp:				
250.0 degrees fahrenheit single response				
End Application:				
Los angeles class ss (688)				
Connection Style:				
Streamlined with one brazing ring err-100				
Valve Operation Method:				
Automatic				
Connection Type:				
Unthreaded internal pipe all ends				
Adjustable Pressure Range:				
+121.0/+135.0 pounds per square inch				
Maximum Operating Pressure:				
400.0 pounds per square inch single response				
Special Features:				
Pressure is to be set at 128 psi				
Material:				
Nickel alloy flow control device				
Material Specification:				
Qq-c-390, alloy d4/d/ federal specification single material response body				
Media For Which Designed:				
Water-oil-gas single response				
Style Designator:				
Err-090				
Furnished Items And Quantity:				
1 lever				
Specification Data:				
81349-mil-v-24332 government specification				
Specification Or Standard:				
B grade				
Shelf Life:				
N/a				

NSN 4820-01-131-0230

Safety Relief Valve - Page 2 of 2



ι	Jnit	Of	Measure:
•	,,,,,	•	moudai c.

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.