
# NSN 4820-01-131-0230

Safety Relief Valve - Page 1 of 2





Pipe Size Accommodated:

0.500 inches all ends

# **Flow Control Device:**

Disk

## Bonnet Type:

Inside spring

# **Bonnet Attachment Method:**

Bolted

# **Disk Loading Method:**

Spring

#### Maximum Operating Temp:

250.0 degrees fahrenheit single response

#### **End Application:**

Los angeles class ss (688)

#### **Connection Style:**

Streamlined with one brazing ring err-100

#### Valve Operation Method:

Automatic

# **Connection Type:**

Unthreaded internal pipe all ends

## Adjustable Pressure Range:

+121.0/+135.0 pounds per square inch

# Maximum Operating Pressure:

400.0 pounds per square inch single response

## **Special Features:**

Pressure is to be set at 128 psi

## Material:

Nickel alloy flow control device

## Material Specification:

Qq-c-390, alloy d4/d/ federal specification single material response body

## Media For Which Designed:

Water-oil-gas single response

#### Style Designator:

Err-090

# Furnished Items And Quantity:

1 lever

## Specification Data:

81349-mil-v-24332 government specification

# **Specification Or Standard:**

B grade

#### Shelf Life:

N/a

# NSN 4820-01-131-0230

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-v-24332 spec.

