NSN 4820-01-131-3043

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-131-3043

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Mounting Position:

Horizontal

Valve Size:

1.500 inches

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

5.000 inches all ends

Face To Face Distance:

5.000 inches

Thickness:

0.440 inches all ends

Bolt Hole Diameter:

0.620 inches all ends

Bolt Circle Diameter:

3.880 inches all ends

Flange Face Design:

Plain all ends

Material:

Copper alloy 922 seat or copper alloy 836 seat

Material Specification:

Qq-c-390, alloy d4 federal specification 1st material response flow control device or qq-c-390, alloy b5 federal specification 2nd material

response flow control device

Style Designator:

Straight through flanged ends

Furnished Items And Quantity:

1 handwheel

Shelf Life:

N/a

NSN 4820-01-131-3043

Lift-check Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A530b0

