NSN 4820-01-131-5915

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-131-5915

Pipe Size Accommodated:
0.500 inches 2nd end
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Streamlined with two brazing rings err-100
Valve Operation Method:
Automatic
Connection Type:
Unthreaded internal pipe 2nd end
Thready Qty Per Inch (tpi):
16 1st end
Adjustable Pressure Range:
+401.0/+500.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.500 inches 1st end
Special Features:
Adjusting ring
Material:
Rubber synthetic packing
Material Specification:
Mil-s-20164 military specification single material response seat
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Thread Series Designator:

Un 1st end

NSN 4820-01-131-5915

Safety Relief Valve - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0

Mil-std (military Standard):

Mil-s-20164 spec.