NSN 4820-01-131-5919

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-131-5919



Flow Control Device: Disk Bonnet Type: Inside spring Bonnet Attachment Method: Bolted Maximum Operating Temp: 450.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round all ends

Connection Type:

Flange all ends

Valve Size:

0.500 inches

Adjustable Pressure Range:

+25.0/+29.0 pounds per square inch

Maximum Operating Pressure:

150.0 pounds per square inch single response

Outside Diameter:

3.500 inches all ends

Thickness:

0.376 inches all ends

First Connection Face To Centerline Distance:

3.250 inches

Second Connection Face To Centerline Distance:

3.250 inches

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.062 inches all ends

Raised Face Diameter:

1.375 inches all ends

Material:

Stainless steel stem

Material Specification:

Astm a216, grade wcb assn standard single material response body

Media For Which Designed:

Oil 1st response

Style Designator:

Err-090

NSN 4820-01-131-5919

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

