## NSN 4820-01-131-7648

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-131-7648

Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
End Application:
Los angeles class ss (688)
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+30.0/+34.0 pounds per square inch
Outside Diameter:
3.500 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.250 inches
Bolt Hole Diameter:
0.625 inches all ends
Second Connection Face To Centerline Distance:
3.250 inches
Bolt Circle Diameter:
2.375 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.375 inches all ends
Material:
Steel uns j03002 body
Style Designator:
Err-090

## NSN 4820-01-131-7648

Safety Relief Valve - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A046b0