NSN 4820-01-131-7650

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-131-7650

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
20.00
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+15.0/+19.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.562 inches all ends
Thickness:
0.375 inches all ends
First Connection Face To Centerline Distance:
3.000 inches
Second Connection Face To Centerline Distance:
3.000 inches
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 federal specification single material response seat
Media For Which Designed:
Air 1st response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

-

NSN 4820-01-131-7650

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0