## NSN 4820-01-132-3497

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type: Inside spring

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-132-3497

g	
Bonnet Attachment Method:	
Bolted	
Maximum Operating Temp:	
425.0 degrees fahrenheit single response	
Valve Operation Method:	
Automatic	
Flange Shape:	
Round all ends	
Connection Type:	
Flange all ends	
Valve Size:	
0.500 inches	
Adjustable Pressure Range:	
+10.0/+14.0 pounds per square inch	
Maximum Operating Pressure:	
250.0 pounds per square inch single response	
Outside Diameter:	
3.500 inches all ends	
Thickness:	
0.376 inches all ends	
First Connection Face To Centerline Distance:	
3.250 inches	
Second Connection Face To Centerline Distance:	
3.250 inches	
Flange Face Design:	
Raised straight 1st end	
Raised Face Height:	
0.062 inches 1st end	
Raised Face Diameter:	
1.375 inches all ends	
Material:	
Stainless steel body	
Media For Which Designed:	
Steam single response	
Style Designator:	
Err-090	
Shelf Life:	
N/a	

## NSN 4820-01-132-3497

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0