## NSN 4820-01-132-4827

Safety Relief Valve - Page 1 of 2

Flow Control Device:

**Bonnet Type:** 

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-132-4827

inside spring
Bonnet Attachment Method:
Bolted
Maximum Operating Temp:
425.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
0.500 inches
Adjustable Pressure Range:
+25.0/+29.0 pounds per square inch
<b>Maximum Operating Pressure:</b>
250.0 pounds per square inch single response
Outside Diameter:
3.500 inches all ends
Thickness:
0.376 inches all ends
First Connection Face To Centerline Distance:
3.250 inches
Second Connection Face To Centerline Distance:
3.250 inches
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.375 inches all ends
Material:
Stainless steel body
Media For Which Designed:
Steam single response
Style Designator:
Err-090
Shelf Life:
N/a

## NSN 4820-01-132-4827

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0