NSN 4820-01-134-2803

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-134-2803

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Maximum Operating Temp:
150.0 degrees fahrenheit single response
End Application:
Vehicle, aircraft refueler r-9
Connection Style:
Streamlined with one brazing ring (tube) err-100
Valve Operation Method:
Automatic
Flange Shape:
Round 1st end
Connection Type:
Unthreaded internal tube 2nd end
Adjustable Pressure Range:
+151.0/+180.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
3.875 inches 1st end
Thickness:
0.344 inches 1st end
Flange Face Design:
Plain 1st end
Outside Diameter Tube Accommodated:
0.750 inches 2nd end
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-281 federal specification single material response stem
Media For Which Designed:
Gas, inert 2nd response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-134-2803

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0