## NSN 4820-01-135-3886

Compressed Gas Regulator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-01-135-3886

Maximum Delivery Pressure:
15.0 pounds per square inch
Mounting Method:
Cylinder
Mounting Position:
Back
Stage Type:
Double
Inlet Fitting Connection Type:
Compressed gas association
Outlet Fitting Thread Direction:
Right-hand
Delivery Pressure Type:
Adjustable
Inlet Fitting Connection Cga Number:
5
320
_
320
320 Outlet Fitting Connection Type:
320 Outlet Fitting Connection Type: Threaded internal pipe
320 Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size:
320 Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size: 0.625 inches
320 Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size: 0.625 inches Inlet Indicator Type:
Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size: 0.625 inches Inlet Indicator Type: Dial pressure gage
Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size: 0.625 inches Inlet Indicator Type: Dial pressure gage Outlet Indicator Type:
Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size: 0.625 inches Inlet Indicator Type: Dial pressure gage Outlet Indicator Type: Dial pressure gage
Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size: 0.625 inches Inlet Indicator Type: Dial pressure gage Outlet Indicator Type: Dial pressure gage Shelf Life:
Outlet Fitting Connection Type: Threaded internal pipe Outlet Fitting Thread Size: 0.625 inches Inlet Indicator Type: Dial pressure gage Outlet Indicator Type: Dial pressure gage Shelf Life: N/a

No Fiig: A514u0