NSN 4820-01-139-1712

Safety Relief Valve - Page 1 of 2

Flow Control Device:

Bonnet Type:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-139-1712

Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
0.750 inches
Adjustable Pressure Range:
+90.0/+140.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Outside Diameter:
3.812 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
2.812 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
2.812 inches
Bolt Circle Diameter:
2.688 inches all ends
Flange Face Design:
Plain all ends
Special Features:
Valve size 0.750 in.

Rubber butadiene-acrylonitrile class nbr flow control device

NSN 4820-01-139-1712

Safety Relief Valve - Page 2 of 2



Style Designator:
Err-090
Furnished Items And Quantity:
1 lever
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A046b0