

View Online at <https://aerobasegroup.com/nsn/4820-01-140-4834>

Flow Control Device:

Disk

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

4 all ends

Valve Operation Method:

Manual

Flange Shape:

Round with holes all ends

Connection Type:

Flange all ends

Features Provided:

Bonnet packing

Valve Size:

1.500 inches

Maximum Operating Pressure:

600.0 pounds per square inch single response

Outside Diameter:

6.120 inches all ends

Face To Face Distance:

12.000 inches

Thickness:

0.810 inches all ends

Bolt Hole Diameter:

0.753 inches all ends

Bolt Circle Diameter:

4.500 inches all ends

Flange Face Design:

Raised straight all ends

Raised Face Height:

0.250 inches all ends

Raised Face Diameter:

2.875 inches all ends

Special Features:

Valve stem adaptor and mating, unattached tee wrench

Material:

Steel flow control device

Material Specification:

Astm a182, grade f22 assn standard single material response flow control device

Media For Which Designed:

Steam single response

Style Designator:

Err-090

Specification Data:

81349-mil-v-17737f government specification

Specification Or Standard:

1 class and 2 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0