

View Online at <https://aerobasegroup.com/nsn/4820-01-143-4568>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Poppet

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

9.0 gallons per minute

**Maximum Operating Temp:**

160.0 degrees fahrenheit single response

**Connection Style:**

G42 flared (tube) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

600.0 pounds per square inch single response

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Opening Pressure Setting:**

50.0 pounds per square inch

**Material:**

Aluminum alloy 2024 body

**Material Specification:**

Qq-a-225/6 federal specification single material response body

**Media For Which Designed:**

Hydraulic fluid, petroleum base single response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 2 military specification single treatment response

**Style Designator:**

Err-090

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A046b0

**Mil-std (military Standard):**

Mil-a-8625 spec.