

View Online at <https://aerobasegroup.com/nsn/4820-01-143-4568>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

9.0 gallons per minute

Maximum Operating Temp:

160.0 degrees fahrenheit single response

Connection Style:

G42 flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Maximum Operating Pressure:

600.0 pounds per square inch single response

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

50.0 pounds per square inch

Material:

Aluminum alloy 2024 body

Material Specification:

Qq-a-225/6 federal specification single material response body

Media For Which Designed:

Hydraulic fluid, petroleum base single response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

Style Designator:

Err-090

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.