NSN 4820-01-147-1307

Globe Valve - Page 1 of 2

Flow Control Device:

Disk



View Online at https://aerobasegroup.com/nsn/4820-01-147-1307

DISK
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
1000.0 degrees fahrenheit 1st response
Valve Operation Method:
Manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Features Provided:
Bonnet packing
Valve Size:
1.000 inches
Maximum Operating Pressure:
285.0 pounds per square inch 2nd response
Outside Diameter:
4.250 inches all ends
Face To Face Distance:
5.000 inches
Thickness:
0.562 inches all ends
Bolt Hole Diameter:
0.625 inches all ends
Bolt Circle Diameter:
3.125 inches all ends
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.062 inches all ends
Raised Face Diameter:
1.938 inches all ends
Special Features:
Loose disc; integral hard faced seat; conventional port; chrome trim
Material:
Steel uns k03504 body

NSN 4820-01-147-1307

Globe Valve - Page 2 of 2

Fiig: A046b0



Material Specification:
Astm a105 assn standard single material response body
Media For Which Designed:
Water-oil-gas 2nd response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No