NSN 4820-01-148-6940

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-148-6940 **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method: Bolted Disk Loading Method:** Spring **Maximum Operating Temp:** 150.0 degrees fahrenheit single response **Connection Style:** G9 plain, optional en (pipe) 1st end **Valve Operation Method:** Manual **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 400.0 pounds per square inch single response **Thread Size:** 0.500 inches 2nd end **Opening Pressure Setting:** 128.0 pounds per square inch **Special Features:** Reducing connector, 0.500 in. Nptf to 0.250 in. flare Material: Copper alloy Media For Which Designed: Steam single response **Style Designator:** Err-090 **Thread Series Designator:**

Npt 1st end

Specification Or Standard:
7 class and a style and 2 type

Shelf Life:

N/a

Unit Of Measure:

--

NSN 4820-01-148-6940

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0