

View Online at <https://aerobasegroup.com/nsn/4820-01-148-9382>

Thread Class:

2a 2nd end

Thread Direction:

Right-hand 2nd end

Flow Control Device:

Disk

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Union

Disk Loading Method:

Spring

Bolt Hole Quantity:

4 1st end

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Connection Style:

Err-090 2nd end

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 1st end

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

11 2nd end

Adjustable Pressure Range:

+65.0/+84.0 pounds per square inch

Maximum Operating Pressure:

100.0 pounds per square inch single response

Thread Size:

2.159 inches 2nd end

Seat Angle:

45.0 degrees 2nd end

Outside Diameter:

4.250 inches 1st end

Thickness:

0.438 inches 1st end

Bolt Hole Diameter:

0.562 inches 1st end

Bolt Circle Diameter:

3.125 inches 1st end

Flange Face Design:

Plain 1st end

Material:

Nickel alloy flow control device

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Thread Series Designator:

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0