NSN 4820-01-149-1834

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-149-1834

Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring Volve Operation Methods
Valve Operation Method:
Automatic
Flange Shape:
Round 2nd end
Connection Type:
Flange 1st end
Valve Size:
1.500 inches
Adjustable Pressure Range:
+30.0/+50.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
5.000 inches 2nd end
Thickness:
0.688 inches 1st end
First Connection Face To Centerline Distance:
4.312 inches
Second Connection Face To Centerline Distance:
3.875 inches
Flange Face Design:
Raised straight 2nd end
Raised Face Height:
0.062 inches 2nd end
Raised Face Diameter:
4.125 inches 1st end
Material:
Rubber butadiene-acrylonitrile class nbr seat
Material Specification:
Astm a216, grade wcb assn standard single material response body
Style Designator:
Err-090
Furnished Items And Quantity:
4 lever

1 lever

NSN 4820-01-149-1834

Safety Relief Valve - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0