## NSN 4820-01-149-3323

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-149-3323

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Valve Operation Method:
Automatic
Flange Shape:
Round 2nd end
Connection Type:
Flange 1st end
Valve Size:
4.000 inches
Adjustable Pressure Range:
+166.0/+183.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Outside Diameter:
9.000 inches 2nd end
Thickness:
1.000 inches 1st end
First Connection Face To Centerline Distance:
9.094 inches
Second Connection Face To Centerline Distance:
7.125 inches
Flange Face Design:
Plain 2nd end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
8.500 inches 1st end
Material:
Steel comp 416 stem
Material Specification:
Astm a216, grade wcb assn standard single material response body
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-01-149-3323

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0