NSN 4820-01-149-5532

Safety Relief Valve - Page 1 of 2

Flow Control Device:



View Online at https://aerobasegroup.com/nsn/4820-01-149-5532

Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Bolt Hole Quantity:
6 all ends
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Valve Operation Method:
Automatic or manual
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Adjustable Pressure Range:
+45.0/+70.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
5.062 inches all ends
Thickness:
0.438 inches all ends
First Connection Face To Centerline Distance:
3.750 inches
Bolt Hole Diameter:
0.562 inches all ends
Second Connection Face To Centerline Distance:
3.750 inches
Bolt Circle Diameter:
3.938 inches all ends
Flange Face Design:
Plain all ends
Material:
Rubber butadiene-acrylonitrile class nbr flow control device
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090

NSN 4820-01-149-5532

Safety Relief Valve - Page 2 of 2



She	lf I	Life	е:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0