# NSN 4820-01-151-3685

Safety Relief Valve - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4820-01-151-3685



Flow Control Device:

Disk

Bonnet Type:

Inside spring

## **Bonnet Attachment Method:**

Bolted

## Maximum Operating Temp:

150.0 degrees fahrenheit single response

### Valve Operation Method:

Automatic

Flange Shape:

Round all ends

#### **Connection Type:**

Flange all ends

Valve Size:

2.000 inches

#### Adjustable Pressure Range:

+156.0/+180.0 pounds per square inch

#### Maximum Operating Pressure:

250.0 pounds per square inch single response

### **Outside Diameter:**

6.500 inches all ends

Thickness:

0.875 inches all ends

### First Connection Face To Centerline Distance:

4.750 inches

### Second Connection Face To Centerline Distance:

4.750 inches

#### Flange Face Design:

Plain all ends

Material:

Nickel alloy flow control device

#### **Material Specification:**

Qq-n-288 federal specification single material response seat

#### Media For Which Designed:

Water-oil-gas single response

Style Designator:

Err-090

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 4820-01-151-3685

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

