NSN 4820-01-151-3685

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-151-3685

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Valve Operation Method:
Automatic
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
2.000 inches
Adjustable Pressure Range:
+156.0/+180.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Outside Diameter:
6.500 inches all ends
Thickness:
0.875 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Second Connection Face To Centerline Distance:
4.750 inches
Flange Face Design:
Plain all ends
Material:
Nickel alloy flow control device
Material Specification:
Qq-n-288 federal specification single material response seat
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-01-151-3685

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0