NSN 4820-01-151-3688

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-151-3688

Flow Control Device:					
Disk					
Disk Loading Method:					
Spring					
Bolt Hole Quantity:					
8 all ends					
Maximum Operating Temp:					
180.0 degrees fahrenheit single response					
Valve Operation Method:					
Automatic					
Flange Shape:					
Round with holes all ends					
Connection Type:					
Flange all ends					
Valve Size:					
4.000 inches					
Adjustable Pressure Range:					
+45.0/+70.0 pounds per square inch					
Maximum Operating Pressure:					
300.0 pounds per square inch single response					
Opening Pressure Setting:					
70.0 pounds per square inch					
Outside Diameter:					
9.000 inches all ends					
Thickness:					
1.062 inches all ends					
First Connection Face To Centerline Distance:					
5.688 inches					
Bolt Hole Diameter:					
0.750 inches all ends					
Second Connection Face To Centerline Distance:					
5.688 inches					
Bolt Circle Diameter:					
7.500 inches all ends					
Flange Face Design:					
Plain all ends					
Material:					
Rubber butadiene-acrylonitrile class nbr flow control device					
Style Designator:					
Err-090					
Furnished Items And Quantity:					

1 lever

NSN 4820-01-151-3688

Safety Relief Valve - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0