NSN 4820-01-151-3750

Fluid Pressure Regulating Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-151-3750

| View Online at https://aerobasegroup.com/nsn/- | 48 |
|--|----|
| Body Material: | |
| Steel, mil-s-15083, grade b | |
| First End Flange Outside Diameter: | |
| 4.875 inches | |
| Body Style: | |
| Straight thru | |
| Stem Material: | |
| Steel, corrosion resisting | |
| First End Connection Type: | |
| Raised face flange | |
| First End Style Designator: | |
| Raised | |
| First End Raised Face Height: | |
| 0.250 inches | |
| First End Raised Face Diameter: | |
| 2.000 inches | |
| First End Flange Shape Style: | |
| Round w/ bolt holes | |
| First End Flange Thickness: | |
| 0.688 inches | |
| First End Bolt Hole Quantity: | |
| 4 | |
| First End Bolt Hole Diameter: | |
| 0.750 inches | |
| First End Bolt Circle Diameter: | |
| 3.500 inches | |
| Second End Relationship With First End: | |
| Identical | |
| Seat Material: | |
| Steel, corrosion resisting | |
| Face To Face Distance: | |
| 8.250 inches | |
| Flow Control Device: | |
| Stem and integral disk | |
| Flow Control Device Material: | |
| Steel, corrosion resisting | |
| End Connection Quantity: | |
| 2 | |
| Outlet Pressure Range: | |
| +2.0/+35.0 pounds per square inch | |
| Regulation Type: | |
| | |

Automatic single stage

NSN 4820-01-151-3750 Fluid Pressure Regulating Valve - Page 2 of 2



| Valve Loading Method: |
|--|
| Spring |
| Maximum Inlet Pressure Rating: |
| 600.0 pounds per square inch |
| Filter: |
| Not included |
| Геmpurature Rating: |
| 500.0 degrees fahrenheit |
| Special Features: |
| Furnished w/welded bent nipple pc.No.39, orifice pc.No.41, and flange pc.No.40 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A21100 |