## NSN 4820-01-152-7703

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-01-152-7703

Flow Control Device:
Disk
Bonnet Type:
Inside spring  Bonnet Attachment Method:
Integral  Maximum Operating Temp:
180.0 degrees fahrenheit single response
Valve Operation Method:
Automatic  Flores Shares
Flange Shape:
Round all ends
Connection Type:
Flange all ends
Valve Size:
4.000 inches
Maximum Operating Pressure:
300.0 pounds per square inch single response
Opening Pressure Setting:
70.0 pounds per square inch
Outside Diameter:
10.000 inches all ends
Thickness:
1.062 inches all ends
First Connection Face To Centerline Distance:
5.812 inches
Second Connection Face To Centerline Distance:
5.812 inches
Flange Face Design:
Plain all ends
Material:
Rubber butadiene-acrylonitrile class nbr flow control device
Material Specification:
Qq-c390, alloy d4/d/ federal specification single material response body
Media For Which Designed:
Water, salt single response
Style Designator:
Err-090
Shelf Life:
N/a
Unit Of Measure:

## NSN 4820-01-152-7703

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0