

View Online at <https://aerobasegroup.com/nsn/4820-01-156-0371>

Body Material:

Bronze, astm b61

First End Flange Outside Diameter:

7.688 inches

Body Style:

Straight thru

Stem Material:

Nickel copper alloy

Media For Which Designed:

Water, salt

First End Connection Type:

Plain face flange

First End Style Designator:

Plain

First End Flange Shape Style:

Round w/ bolt holes

First End Flange Thickness:

1.000 inches

First End Bolt Hole Quantity:

8

First End Bolt Hole Diameter:

0.688 inches

First End Bolt Circle Diameter:

6.562 inches

Second End Relationship With First End:

Identical

Seat Material:

Nickel copper alloy

Face To Face Distance:

14.500 inches

Flow Control Device:

Disk

Flow Control Device Material:

Rubber, buna-n

End Connection Quantity:

2

Outlet Pressure Range:

+25.0/+60.0 pounds per square inch

Regulation Type:

Automatic single stage

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

250.0 pounds per square inch

Filter:

Not included

End Application:

Oliver perry class ffg, spruance class dd (963), kidd class ddg, wasp class lhd, whidbey island class lsd, tarawa class lhd, osprey class mhc, forrestal class cv.

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100